



tesa® Professional 51960

Extra Strong - Double-Sided Removable

Product Information

Double-sided carpet tape for professional users - removable

Product Description

tesa® Professional 51960 is the double-sided, extra-strength adhesive carpet tape for professional use. The adhesive sides of the double-sided carpet tape offer varying adhesive strengths, meaning that it holds carpets and rugs in place securely, but can also be removed from the surface underneath with very little difficulty and without leaving any residue. The double-sided carpet tape can be torn by hand and offers craftsmen a high level of convenience. It comprises a fibre-reinforced PP film in combination with an acrylate adhesive mass. Neither moisture nor weak chemicals will damage the adhesive tape.

Application Fields

- Indoor applications
- For textile and resilient floor coverings
- Can be used on many surfaces
- Border conglutination of floor coverings

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	PP film reinforced by fabric	• Total thickness	248 µm
• Type of adhesive	tackified acrylic		

Properties/Performance Values

• Elongation at break	80 %	• Chemical Resistance	very good
• Tensile strength	30 N/cm	• Humidity resistance	very good

Adhesion to Values

• Steel	4.7 N/cm
---------	----------

Additional Information

According to DIN 18365 the surface has to be even, clean, permanently jointed and dry as well as free of oil or wax

(Not suitable for natural stone)



tesa® Professional 51960

Extra Strong - Double-Sided Removable

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51960>