



tesa® Professional 60077 PE Sealing Flex Plus Tape

Product Information

tesa® 60077 PE Sealing Flex Plus Tape

Product Description

The flexible PE sealing tape tesa® 60077 with its particular adhesive strength is ideally suited for airtight seals of overlapping vapor barrier foils. The vapor barrier tape helps efficiently protect buildings from humidity that might enter through the roof. For sealing wall penetrations, e.g., when laying pipes and cables, the sealing tape is a reliable helper. Due to its flexible backing, the fibers inside and a width of 50mm, application is easy and fast. Its high age resistance allows the sealing adhesive tape to be used in challenging environments as well. Furthermore, the sealing tape has very low emissions (GEV-EMICODE certificate).

Application Fields

- Flexible, PE-based sealing tape
- Protects buildings against humidity through airtight sealing of vapor barrier foils (according to (gem. DIN 4108-11)
- Vapor barrier tape for new buildings and renovations of existing roofs
- Indoor and outdoor application (according to P-mark certificate): insulation under, between or over the rafters
- Sealing adhesive tape also suited to seal wall penetrations when laying pipes and cables
- Extremely high and permanent adhesive strength
- Easy and time-saving application

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	PE film	• Total thickness	290 µm
• Type of adhesive	acrylic		



tesa® Professional 60077

PE Sealing Flex Plus Tape

Product Information

Additional Information

tesa® 60077 Seal Flex is a flexible and powerfully adhesive PE sealing tape ideally suited for airtight seals of vapor barrier foils.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60077>