

## PRELIMINARY Product Information

### Standard grade tensilized non-staining strapping tape

tesa® 4287 PV10 is a tensilized polypropylene strapping tape with a synthetic rubber adhesive system. The MOPP-film backing makes tesa® 4287 PV10 conformable.

#### Benefits:

- tesa® 4287 PV10 exhibits good tensile strength with low elongation at the same time.
- The synthetic rubber adhesive offers excellent tack, as well as excellent adhesion to polar and non-polar substrates.
- The strapping tape features a very short dwell time until reaching its final adhesive strength
- After use, the tape offers a residue-free removal and will leave no discoloration.

### Main Application

- tesa® 4287 PV10 is used in a variety of industrial applications: palletizing, belting of electronic components, bundling and closure of shipping cartons
- The strapping tape offers good temperature-resistance
- tesa® 4287 PV10 features residue-free removability

### Technical information (average values)

The values in this section should be considered as average figures or typical only and should not be used for specification purposes.

#### Technical Data

- |                       |                  |                    |          |
|-----------------------|------------------|--------------------|----------|
| • Backing material    | MOPP             | • Total thickness  | 79 µm    |
| • Type of adhesive    | synthetic rubber | • Tensile strength | 180 N/cm |
| • Elongation at break | 35%              |                    |          |

#### Adhesion to

- Adhesion to steel 6 N/cm

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.